

IDENTITYTM
SYSTEMS



A New Beginning!

PERFORMANCE SPECIFICATIONS

| | ID 386 33 MHz | ID 386 25 MHz | ID 386 20 MHz | ID 386 16 MHz | ID 386 SX | ID 286 12 MHz |
|-----------------------|-------------------------|-------------------------|----------------------|--------------------|-------------------|---------------------|
| Processor | 80386 | 80386 | 80386 | 80386 | 80386-5X | 80286-12 |
| CPU Clock | 33 MHz | 25 MHz | 20/6 MHz | 16/6 MHz | 16/8 MHz | 12/6 MHz |
| Form Factor | AT Standard | AT Standard | AT Standard | AT Standard | Baby AT | AT Standard |
| CO-Processor (option) | 80387/weitek3167 | 80387/weitek3167 | 80387 | 80387 | 80387-SX | 80287 |
| CO-Processor Clock | 33 MHz Selectable | 25 MHz Selectable | 20/6 MHz | 16 MHz | 16 MHz | 12/6 MHz |
| Fab Type | 8 Layer | 8 Layer | 8 Layer | 6 Layer | 4 Layer | 4 Layer |
| 8 bit AT Slot | 1 | 1 | 1 | 1 | 2 | 2 |
| 16/8 bit ISA Slot | 4 | 4 | 6 | 6 | 6 | 6 |
| 32 bit bus Slot | 2 | 2 | 1 | 1 | N/A | N/A |
| Bus Speed | 8/10/12/16 MHz | 8/10/12/16 MHz | 8/10 MHz | 8/6 MHz | 8 MHz | 12/6 MHz |
| Memory Type | Simm Dram | Simm Dram | Simm Dram | Dip Dram | Simm Dram | Dip Dram |
| Wait States | 0 | 0 | 0 | 0 | 0 using page | 1 or 0 |
| Memory Speed | 80NS | 100NS | 100NS | 120NS | 100NS | 100NS |
| Memory Configuration | 1/2/4/8/16/32 MBytes | 1/2/4/8/16/32 MBytes | 1/2/4/8/16 MBytes | 1/2/6/10 MBytes | up to 8 MBytes | 512/640/1 MBytes |
| Variable Cache | 0/16/32/128 | 0/16/32/128 | 64 only | 64 only | None | None |
| MIPS | 7.5 | 5.7 | 4.3 | N/A | N/A | 1.9 |
| Landmark | 53 | 41.3 | 29.6 | 23.5 | 19 | 14 |
| Limited Warranty* | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year |
| Manufactured in USA | yes | yes | yes | yes | yes | yes |

Available in Tower and Desk Top Cases

*Limited Warranty

- | | |
|--|---|
| <input type="checkbox"/> PRODUCTION quality controlled. | <input type="checkbox"/> Available in speeds up to 33 MHz. |
| <input type="checkbox"/> Highly trained technical support staff. | <input type="checkbox"/> Quality RAM products incorporated. |
| <input type="checkbox"/> All system boards tested and burned-in at 60°C (140°F) to insure quality and reliability. | <input type="checkbox"/> FCC certified units. |
| <input type="checkbox"/> State of the art components incorporated in each system. | <input type="checkbox"/> Special configurations available. |



1355 GLENVILLE
RICHARDSON, TX 75081
PHONE: (214) 699-8300 • 800-888-DISK
FAX: (214) 699-8404

FOR FURTHER INFORMATION, PLEASE CONTACT: